

ParkGard® LED Arrow and Counting Display Panel PL-01

Description

Arrow and counting display panel, robust, maintenance-free and energy-saving thanks to LED technology.

The easy mounting is due to the flat and stable aluminium frame

Application

The arrow and counting display is used in underground garages and multi-storey car parks for guiding the vehicles to the next unoccupied parking space. The car driver recognizes immediately how many spaces are free, and is guided by means of the directional arrows to the next unoccupied parking space. If already completely occupied the respective area is marked by a red X. The manager of the garage can also lock up corresponding sections herewith.




Features

- LED – displays max. 4-digit
- Activation via RS485 bus
- Operating voltage 24 VAC/DC
- Energy-saving
- Long life expectancy (100.000 h)
- Different text colours (green, white, blue)
- Character height 100 mm
- Stable aluminium profile
- Flat design 30 mm
- Simple mounting and terminal connection
- Low weight, therefore one-man installation possible
- Suitable for ceiling and wall fastening
- Brightness dimmable

Ordering Information

PL-01-XX-XX-XXX



2. Element: Counting display

- 1XX LED colour green
- 2XX LED colour white
- 3XX LED colour blue
- X1X Number of digits of the LED display
1 = 1-digit, 2 = 2-digit etc.
- XX1 1 = Display 0-9
2 = Display 0-9 und X

1. Element: Arrow

- 01 LED arrow straight (green) / X (red)
- 02 LED arrow 45° (green) / X (red)
- 03 LED arrow straight (green) / arrow (red)
- 04 LED arrow 45° (green) / arrow (red)

Dimensions

- 01 250 x 250 x 30mm
- 02 500 x 250 x 30mm
- 03 750 x 250 x 30mm

Example: Arrow and counting display panel, 500 x 250 x 30mm with arrow display 45° and X, as well as with 3-digit counting display in green without X display.

Ordering number: **PL-01-02-02-131**

Illuminated displays are also available on request in various dimensions and versions.